

BASEBETON PAINT - PRIMER

USER MANUAL + TECHNICAL DATA SHEET

PRODUCT DESCRIPTION:

Basebeton Paint – Primer is a ready-to-use Primer which ensures a good preparation on the surface for Basebeton Paint. Basebeton Paint – Primer provides an equal absorption, an improved attachment with the surface and extends the lifespan of Basebeton Paint.

USAGE:

Basebeton Paint – Primer is suitable for:

- Painted walls
- Plastered walls
- Glass fiber wallpaper
- Spachtelputz
- MDF

Basebeton Paint – Primer is specifically designed for indoor usage.

METHOD OF APPLICATION

PREPARATION (day 1)

The surface on which Basebeton Paint – Primer is applied should always be clean and dry. A shiny surface or veneered wood should always be sanded first so the coating layer is removed.

NOTE:

Basebeton Paint – Primer does not actively adhere to surfaces of oiled wood or vinyl wallpaper. Therefore these surfaces are not suitable for applying Basebeton Paint – Primer.

APPLICATION CONDITIONS

- Required room temperature of 7°C - 27°C.
- Maximum humidity of the surface of 4%

APPLYING THE FIRST LAYER OF BASEBETON PAINT – PRIMER

Stir the Basebeton Paint – Primer well before applying the first layer.

Basebeton Paint – Primer can be applied with a block brush or a micro fibre roller. In contradiction of traditional primers, Basebeton Paint – Primer does not have to be completely opaque after 1 layer. It is sufficient when the Primer has covered the entire surface. Allow Basebeton Paint – Primer to dry for at least 12 hours.

If a surface absorbs a lot of paint, such like wood or a plastered wall, a second layer of Basebeton Paint – Primer should be applied. For highly absorbent surfaces it is possible to dilute the Basebeton Paint - Primer with 20% water.

CONSUMPTION:

With 1 kilogram of Basebeton Paint – Primer it is possible to treat a surface of 6 m² in 1 layer.

STORAGE PERIOD:

Basebeton Paint – Primer can be stored up to 12 months, provided it is stored closed and dry.

SUSTAINABILITY



Basebeton Paint – Primer consists of 87% ecologically responsible substances.

ADDITIONAL HEALTH AND SAFETY INFORMATION

For information and advice on the safe handling, storage and disposal of chemical products, users of these

products should refer to the most recent Material Safety Data Sheet with regard to physical, ecological, toxicological and other safety-related data.



Stone Age B.V.
Butaanstraat 10
7463 PG RIJSSEN - Nederland

DISCLAIMER

This information and in particular the recommendations regarding the application and use of Stone Age products, is provided in good faith based on our current experience(s) and product knowledge. This information applies with respect to products stored, handled and applied under normal conditions and correctly, in accordance with Stone Age's advice. In practice, differences in materials, substrates and actual (working) conditions on site are such that no guarantee of merchantability or suitability for a particular purpose, nor any liability (arising from any legal relationship whatsoever) can be derived from this information or from any advice (whether verbal or written) given by Stone Age. The user of the products should test the suitability of the products for the intended application and purpose. Stone Age reserves the right to change the properties of its products at any time. The property rights of both Stone Age and third parties must be respected. All orders to Stone Age are subject to the currently applicable sales and delivery conditions.

CE MARK

The harmonized European standard EN 13 813 „Screed material and floor screeds – screeds – material properties and requirements” specifies requirements for screeds for use with floor constructions. Structural screeds or coatings, for example those contributing to the load bearing capacity of the construction, are excluded from this standard. Both synthetic resin floors and cement-bonded screeds are covered by these specifications. They must be CE-labelled according to Annex ZA. 3, Table ZA. 1.5 and 3.3 and comply with the requirements of the Construction Products Directive (89/106)